


Line Lite International BV---CDE Technology BV


www.linelite.com Contact Menno Rottenberg info@linelite.com

www.cdebv.com Contact Paul van den Hoogen info@cdebv.com





Double side interlighting led grow light for Supplementary Lighting

LC-SR075W		Item	Parameters	Item	Parameters	
Unit Price	Euro/pcs 165,00	Power	75W (0.5Wx150)	Wavelength	660nm:460nm	
MOQ	1 pcs	Input Voltage	AC85~265V	Color Ratio	R:B=4:1	
		Frequency	50/60 Hz	PPFD	26μmol/m ² /s/H0.6m	
		LED Source	150pcs 0.5W LED	Suggest Height	0.3m	
		Working temp	-20~50°C	Irradiation Area	0.45 m ²	
		IP Grade	IP65	Beam Angle	120 degree	
		Lifespan	50,000 hours	Dimension	1495*75*53(mm)	
		Warranty	2years	Nett Weight	2.8kg/pc	
		Application	Greenhouses, hydroponics, Agro/Horticulture			


LC-SR150W		Item	Parameters	Item	Parameters	
Unit Price	Euro/pcs335,00	Power	150W (0.5Wx300)	Wavelength	660nm:460nm	
MOQ	1 pcs	Input Voltage	AC85~265V	Color Ratio	R:B=4:1	
		Frequency	50/60 Hz	PPFD	26μmol/m ² /s/H0.6m	
		LED Source	300pcs 0.5W LED	Suggest Height	0.3m	
		Working temp	-20~50°C	Irradiation Area	0.9 m ²	
		IP Grade	IP65	Beam Angle	120 degree	
		Lifespan	50,000 hours	Dimension	2986*75*53(mm)	
		Warranty	2years	Nett Weight	5.6kg/pc	
		Application	Greenhouses, hydroponics, Agro/Horticulture			



LED Grow Light Series

LC120		Items	Parameters	Items	Parameters	
Unit Price	Euro/pcs 245,00	Power	120W (30Wx4)	Wavelength	660nm:460nm	
MOQ	1 pcs	Input Voltage	AC85~265V	Color Ratio	R:B =4:1	
		Frequency	50/60 Hz	PPFD	50μmol/m ² /s/H1m	
		LED Source	4pcs 30w integrated LED	Suggest Height	1.2~1.5m	
		Working temp	-20~50°C	Irradiation Area	4.6 m ² ~7.2 m ²	
		IP Grade	IP44	Beam Angle	90 degree	
		Lifespan	50,000 hours	Nett Weight	3.6kg/pcs	
		Warranty	2years	Application	Greenhouses, hydroponics, Agro/Horticulture, home-usage	


LC240		Items	Parameters	Items	Parameters	
Unit Price	Euro/pcs 345,00	Power	240W (60Wx4)	Wavelength	660nm:460nm	
MOQ	1 pcs	Input Voltage	AC85~265V	Color Ratio	R:B =3:1	
		Frequency	50/60 Hz	PPFD	122μmol/m ² /s/H1m	
		LED Source	4pcs 60w integrated LED	Suggest Height	2.0~2.3m	
		Working temp	-20~50°C	Irradiation Area	12.8 m ² ~17.0 m ²	
		IP Grade	IP44	Beam Angle	90 degree	
		Lifespan	50,000 hours	Dimension	283*283*75(mm)	
		Warranty	2years	Nett Weight	4.6kg	
		Application	Greenhouses, hydroponics, Agro/Horticulture, home-usage			


LC300		Items	Parameters	Items	Parameters
Unit Price	Euro/pcs 375,00	Power	300W (75Wx4)	Wavelength	660nm:460nm
MOQ	1 pcs	Input Voltage	AC85~265V	Color Ratio	R:B =3:1


	Frequency	50/60 Hz	PPFD	137 μ mol/m ² /s/H1m
	LED Source	4pcs 75w integrated LED	Suggest Height	2.0~2.3m
	Working temp	-20~50°C	Irradiation Area	12.8m ² ~17.0m ²
	IP Grade	IP44	Beam Angle	90 degree
	Lifespan	50,000 hours	Dimension	283*283*75(mm)
	Warranty	2years	Nett Weight	4.8kg
	Application	Greenhouses, hydroponics, Agro/Horticulture, home-usage		

LC-300Z7		Items	Parameters	Items	Parameters
Unit Price	Euro/pcs 435,00	Power	300W (75Wx4)	Wavelength	660nm,630nm,610nm,440nm,470nm,730nm,380nm
MOQ	1 pcs	Input Voltage	AC85~265V	Color Ratio	30:16:2:8:8:6:2
 	Frequency	50/60 Hz	PPFD	137 μ mol/m ² /s/H1m	
	LED Source	4pcs 75w integrated LED	Suggest Height	2.0~2.3m	
	Working temp	-20~50°C	Irradiation Area	12.8m ² ~17.0m ²	
	IP Grade	IP44	Beam Angle	90 degree	
	Warranty	2years	Nett Weight	4.8kg	
	Application	Greenhouses, hydroponics, Agro/Horticulture, home-usage			


FS LED Grow Light Series

LC-FSC600		Items	Parameters	Items	Parameters
Unit Price	Euro/pcs 695,00	Power	600W (150Wx4)	Wavelength	380~840nm
MOQ	1 pcs	Input Voltage	AC85~265V	Color Ratio	full spectrum
		Frequency	50/60 Hz	PPFD	90degree: 116μmol/m ² /s/H1.5m
		LED Source	4x 150w COB LED	Suggest Height	2m
		Working temp	-20~50°C	Irradiation Area	7.6m ² ~14.4m ²
		IP Grade	IP44	Beam Angle	90/120/180 degree
		Lifespan	50,000 hours	Dimension	550*388*187(mm)
		Warranty	2years	Nett Weight	13kg/pcs
		Application	Higher plants		


LC-FSC300		Items	Parameters	Items	Parameters
Unit Price	Euro/pcs 375,00	Power	300W (75Wx4)	Wavelength	380~840nm
MOQ	1 pcs	Input Voltage	AC85~265V	Color Ratio	full spectrum
		LED Source	4pcs 75w integrated LED	Suggest Height	2.0~2.3m
		Working temp	-20~50°C	Irradiation Area	12.8m ² ~17.0m ²
		IP Grade	IP44	Beam Angle	90 degree
		Lifespan	50,000 hours	Dimension	283*283*75(mm)
		Warranty	2years	Nett Weight	4.8kg
		Application	Higher plants		

LC-FSC150		Items	Parameters	Items	Parameters
Unit Price	Euro/pcs 235,00	Power	150W (150Wx1)	Wavelength	380~840nm
MOQ	2 pcs	Input Voltage	AC85~265V	Color Ratio	full spectrum
		Frequency	50/60 Hz	PPFD	90degree: 59μmol/m ² /s/ H1.5m
		LED Source	1x 150w COB LED	Suggest Height	1.5m
		Working temp.	-20~50°C	Irradiation Area	4.0m ² ~7.2m ²
		IP Grade	IP44	Beam Angle	90/120/180 degree
		Lifespan	50,000 hours	Dimension	253*193*115(mm)
		Warranty	2years	Nett Weight	3.3kg/pcs
		Application	Higher plants		


par30 7w led grow light with E27

LC-PA007W-01		Item	Parameters	Item	Parameters
Unit Price	Euro/pcs 15,00	Power	7W	Wavelength	660nm:460nm
MOQ	10 pcs	Input Voltage	AC85~265V	Color Ratio	R:B=5:2
		Frequency	50/60 Hz	PPFD	199umol/m ² /s
		LED Source	7*1w high power led	Suggest Height	0.3m
		Working temp	-20~50°C	Substrate Borad	Aluminium Board
		IP Grade	IP44	Beam Angle	60 degree
		Lifespan	50,000 hours	Dimension	78* φ 94(mm)
				Base	E27
		Application	Greenhouses, hydroponics, Agro/Horticulture, home-usage		


12W Par38 LED Grow Light with E27

LC-PA012W-01		Item	Parameters	Item	Parameters
Unit Price	Euro/pcs 21,50	Power	12W	Wavelength	660nm:460nm
MOQ	10 pcs	Led chip Brand	Epileds	Chip size	32mil, 40mil
		Input Voltage	AC85~265V	Color Ratio	R:B=3:1
		Frequency	50/60 Hz	PPFD	112μmol/m ² /s
		LED Source	12*1w high power led	Suggest Height	0.6m
		Working temp	-20~50°C	Substrate Borad	Aluminium Borad
		IP Grade	IP44	Beam Angle	60 degree
		Lifespan	50,000 hours	Dimension	116* φ 118.5(mm)
		Package	27pc/carton	Base	E27
		Warranty	2years	Nett Weight	0.555 kg/pc
		Application	Greenhouses, hydroponics, Agro/Horticulture, home-usage		


18W Par38 LED Grow Light for Flowering


LC-FL018W-01		Item	Parameters	Item	Parameters
Unit Price	Euro/pcs 45,00	Power	18W	Wavelength	660nm:730nm
MOQ	5 pcs	Input Voltage	AC85~265V	Color Ratio	R:IR=2:1
		Frequency	50/60 Hz	PPFD	26μmol/m ² /s/H1m
		LED Source	1pc 18W COB LED	Suggest Height	1m
		Working temp	-20~50°C	Irradiation Area	3.0m ²
		IP Grade	IP44	Beam Angle	90 degree
		Lifespan	50,000 hours	Dimension	119* φ 120(mm)
				Base	E27
		Warranty	2years	Nett Weight	0.365 kg/pc
		Application	Greenhouses, hydroponics, Agro/Horticulture, home-usage		


36w Wall Washer LED Grow Light for Supplementary Lighting

LC-WL036W-01		Item	Parameters	Item	Parameters
Unit Price	Euro/pcs 85,00	Power	36W (1Wx36)	Wavelength	400nm-840nm
MOQ	1 pcs	Input Voltage	AC85~265V	Color Ratio	full spectrum
		Frequency	50/60 Hz	PPFD	80μmol/m ² /s/H0.6m
		LED Source	36pcs 1W high powerLED	Suggest Height	0.6m
		Working temp	-20~50°C	Irradiation Area	1.2m ²
		IP Grade	IP65	Beam Angle	90 degree
		Lifespan	50,000 hours	Dimension	1030*48*99(mm)
		Warranty	2years	Nett Weight	1.95kg/pc
		Application	Greenhouses, hydroponics, Agro/Horticulture		


LED Tube Grow Light Series


LC-T8010W-11		Items	Parameters	Items	Parameters
Unit Price	Euro/pcs 19,00	Power	10W(1Wx10)	Wavelength	660nm:460nm
MOQ	1 pcs	Input Voltage	AC85~265V	Color Ratio	R:B=4:1
		Frequency	50/60 Hz	PPFD	20μmol/m²/s
		LED Source	10pcs 1W high power LED	Suggest Height	0.3m
		Working temp	-20~50°C	Irradiation Area	0.6 m²
		IP Grade	IP44	Socket	D-shape with connector
		Lifespan	50,000 hours	Dimension	600*34*36(mm)
		Warranty	2years	Nett Weight	0.38kg/pcs
		Application	Greenhouses, hydroponics, Agro/Horticulture		
Options: LC-T8010W-12 (R:B=4:1) / LC-T8010W-13 (R:B:W=2:1:1) / LC-T8010W-14 (R:B:Y=2:1:1), LC-T8010W-15 (R:B:W=3:1:1) / LC-T8010W-16(R:B:Y=3:1:1) upon request					


LC-T8020W-11		Items	Parameters	Items	Parameters
Unit Price	Euro/pcs 31.50	Power	20W(1Wx20)	Wavelength	660nm:460nm
MOQ	10 pcs	Input Voltage	AC85~265V	Color Ratio	R:B=4:1
		Frequency	50/60 Hz	PPFD	20μmol/m²/s
		LED Source	20pcs 1W high power LED	Suggest Height	0.3m
		Working temp	-20~50°C	Irradiation Area	1.2 m²
		IP Grade	IP44	Socket	D-shape with connector
		Lifespan	50,000 hours	Dimension	1205*34*36(mm)
		Warranty	2years	Nett Weight	0.45kg/pcs
		Application	Greenhouses, hydroponics, Agro/Horticulture		
Options: LC-T8020W-12 (R:B=4:1) / LC-T8020W-13 (R:B:W=2:1:1) / LC-T8020W-14 (R:B:Y=2:1:1), LC-T8020W-15 (R:B:W=3:1:1) / LC-T8020W-16(R:B:Y=3:1:1) upon request					


LC-T8020W-05		Items	Parameters	Items	Parameters
Unit Price	Euro/pcs 32,00	Power	20W(1Wx20)	Wavelength	660nm:460nm:10000K-12000K
MOQ	10 pcs	Input Voltage	AC85~265V	Color Ratio	R:B:W=3:1:1
		Frequency	50/60 Hz	PPFD	20μmol/m²/s
		LED Source	20pcs 1W high power LED	Suggest Height	0.3m
		Working temp	-20~50°C	Irradiation Area	1.2 m²
		IP Grade	IP44	Socket	G13
		Lifespan	50,000 hours	Dimension	∅ 28*1205(mm)
		Warranty	2years	Nett Weight	0.39 kg
		Application	Greenhouses, hydroponics, Agro/Horticulture		
Options: LC-T8020W-01 (R:B=3:1) / LC-T8020W-02 (R:B=4:1) / LC-T8020W-03 (R:B:W=2:1:1) / LC-T8020W-04 (R:B:Y=2:1:1) / LC-T8020W-06(R:B:Y=3:1:1) can be made, but should be additional inquiry					

LED Strip Grow Light Series

LC-SF014W-01		Items	Parameters	Items	Parameters
Unit Price	Euro/roll 75,00	Power	72w(14.4w/m)	Wavelength	660nm:460nm
MOQ	1 roll	Input Voltage	DC12V	Color Ratio	R:B=4:1
		Current	6A	PPFD	16μmol/m²/s
		LED Source	5050SMD LED	Suggest Height	0.2m
		LED Qty	60pcs/mX5=300pcs	Irradiation Area	3 m²
		Working temp	-20~50°C	Dimension	5000*10*4(mm)(5m/roll)
		IP Grade	IP65	Nett Weight	0.187kg
		Warranty	1years	Lifespan	50,000 hours
		Application	Greenhouses, hydroponics, Agro/Horticulture		
Options: VQ-GLSF014W-02 (R:B=4:1) can be made, should be inquiry additional					

LC-SR007W-01		Items	Parameters	Items	Parameters	
Unit Price	Euro/pcs 15,00	Power	7.2W	Wavelength	660nm:460nm	
MOQ	1 pcs	Input Voltage	DC12V	Color Ratio	R:B=4:1	
		Current	0.6A	PPFD	20µmol/m²/s	
		LED Source	5050SMD LED	Suggest Height	0.2m	
		LED Qty	30 pcs	Irradiation Area	0.3 m²	
		Working temp	-20~50°C	Dimension	500*15*7(mm)	
		IP Grade	IP65	Nett Weight	0.095kg/pcs	
		Warranty	2years	Lifespan	50,000 hours	
		Application	Greenhouses, hydroponics, Agro/Horticulture			
		Options: VQ-GLSR007W-02 (R:B=4:1) can be made, should be inquiry additional				

LC-SR014W-01		Items	Parameters	Items	Parameters	
Unit Price	Euro/pcs 27,50	Power	14.4W	Wavelength	660nm:460nm	
MOQ	10 pcs	Input Voltage	DC12V	Color Ratio	R:B=4:1	
		Current	1.2A	PPFD	20µmol/m²/s	
		LED Source	5050SMD LED	Suggest Height	0.2m	
		LED Qty	60 pcs	Irradiation Area	0.6 m²	
		Working temp	-20~50°C	Dimension	1000*15*7(mm)	
		IP Grade	IP65	Nett Weight	0.18kg/pcs	
		Warranty	2years	Lifespan	50,000 hours	
		Application	Greenhouses, hydroponics, Agro/Horticulture			
		Options: VQ-GLSR014W-02 (R:B=4:1) can be made, should be inquiry additional				

LC-SR028W-05		Items	Parameters	Items	Parameters	
Unit Price	Euro/pcs 45,00	Power	28.8W	Wavelength	660nm:460nm	
MOQ	5 pcs	Input Voltage	DC12V	Color Ratio	R:B: W=2:1 :1	
		Current	2.4A	PPFD	25µmol/m²/s	
		LED Source	5050SMD LED	Suggest Height	0.25m	
		LED Qty	120pcs	Irradiation Area	0.8 m²	
		Working temp	-20~50°C	Dimension	1040*27*19(mm)	
		IP Grade	IP65	Nett Weight	0.45kg/pcs	
		Warranty	2years	Lifespan	50,000 hours	
		Application	Greenhouses, hydroponics, Agro/Horticulture			

Terms & conditions:

- 1) Delivery Base: FOB our warehouse in Holland
- 2) We ship you upon receipt of your Payment.
- 3) Delivery Time is ex Holland max 10 working days upon receipt of your Payment and order confirmation.
- 4) Warranty: 2 years (flexible led grow light strip is 1 year)